

KERN OKO 178



The fully-equipped reflected and transmitted light microscope for numerous applications in metallurgy



Category

Brand	Optics
Product category	Microscope
Product group	Metallurgical microscope
Product family	OKO-1

Construction

Dimension (W×D×H)	550×200×460 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	0:100 80:20
Contrasting methods	Bright field Polarisation
Standard objectives	5× 10× 20× 50×
Lens quality	Infinity semi apochromatic
Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular

Ocular type	Eyeiece HWF 10 x / Ø 22mm with anti-fungus, high eye point
Ocular field width	WF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	22 mm
Ocular diameter	30 mm

Objective

Objectives - Details	Objective Infinity Plan Semi Apochromatic 10 x ... LWD Objective Infinity Plan Semi Apochromatic 20 x ... LWD Objective Infinity Plan Semi Apochromatic 5 x / ... LWD Objective Infinity Plan Semi Apochromatic 50 x ... LWD
Objectives magnifications	5 x / 10 x / 20 x / 50 x

Illumination

Illuminance	Reflected light Transmitted light
Illumination type incident light	LED
Illumination type transmitted light	LED
Illumination intensity incident light	5 W
Illumination intensity transmitted light	5 W
Illumination dimmable	Incident light + Transmitted light, separate
Koehler illumination	✓
Filter possible	✓
Aperture diaphragm	✓
Field diaphragm	✓

Focussing

Field of view [Min]	0,18 mm
Field of view [Max]	3,6 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

KERN OKO 178



The fully-equipped reflected and transmitted light microscope for numerous applications in metallurgy

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
Plug-in power supply / adapter for countries - optional	UK
	US
	CH
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	520×470×430 mm
Shipping method	Parcel service
Net weight approx.	12 kg
Gross weight approx.	16 kg
Shipping weight	21 kg

Pictograms

STANDARD

