KERN OLM 170



The inverted metallurgical microscope for professional applications



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Metallurgical microscope
Product family	OLM-1
Construction	
Dimension (W×D×H)	470×240×330 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	45°
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Polarisation
Standard objectives	5× 10× 20× 50×
Lens quality	Infinity Plan
Nosepiece screw-in locations	4
Interpupillary distance [Min]	48 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-6
Diopter adjustment [Max]	6

Ocular

Ocular type	Eyepiece HWF 10 x / Ø 20mm with anti-fungus, high eye point
Ocular field width	HWF
Eye point	High Eye Point

Ocular magnifications	10 x
Ocular visual field	20 mm
Ocular diameter	23,2 mm
Objective	
Objectives - Details	Objective Infinity Plan 10 x / 0,25 LWD, anti- fungus Objective Infinity Plan 20 x / 0,4 LWD, anti-fungus Objective Infinity Plan 5 x / 0,13 LWD, anti- fungus Objective Infinity Plan 50 x / 0,75 spring, LWD, anti-fungus
Objectives magnifications	5 x / 10 x / 20 x / 50 x
Illumination	
Illuminance	Reflected light
Illumination type incident light	LED
Illumination intensity incident light	5 W
Illumination dimmable	Incident light
Filter possible	\checkmark
Focussing	
Focussing Field of view [Min]	0,4 mm
	0,4 mm 4 mm
Field of view [Min] Field of view [Max] Torque regulation	-
Field of view [Min] Field of view [Max]	4 mm
Field of view [Min] Field of view [Max] Torque regulation	4 mm 🗸
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum	4 mm ✓ 0,002 mm coaxial coarse and fine
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism	4 mm ✓ 0,002 mm coaxial coarse and fine
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply	4 mm ✓ 0,002 mm coaxial coarse and fine drive
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Supplied power supply	4 mm ✓ 0,002 mm coaxial coarse and fine drive Power supply unit
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Supplied power supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the	4 mm ✓ 0,002 mm coaxial coarse and fine drive Power supply unit Power adapter
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	4 mm ✓ 0,002 mm coaxial coarse and fine drive Power supply unit Power adapter EURO EURO
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Plug-in power supply type Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply /	4 mm ✓ 0,002 mm coaxial coarse and fine drive A Power supply unit Power adapter EURO EURO UK 100 V - 240 V, 50 / 60
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max]	4 mm ✓ 10,002 mm coaxial coarse and fine drive Mower supply unit Power adapter EURO UK 100 V - 240 V, 50 / 60 Hz
Field of view [Min] Field of view [Max] Torque regulation Fine drive minimum Focusing mechanism Power Supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Input voltage power supply / power [Max] Input voltage device / power [Max]	4 mm ✓ 0,002 mm coaxial coarse and fine drive A Power supply unit Power adapter EURO UK 100 V - 240 V, 50 / 60 Hz 5 V, 1 A Inside plus, outside

KERN OLM 170



The inverted metallurgical microscope for professional applications

Storage temperature [Max]	40 °C
Approval	
CE mark	1
Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	500×420×300 mm
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	9 kg
Shipping weight	12,6 kg

Pictograms

STANDARD

