## **KERN OZM 982**



Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace



| Category          |                       |
|-------------------|-----------------------|
| Brand             | Optics                |
| Product categoriy | Microscope            |
| Product group     | Stereo microscope set |
| Product family    | OZM-9                 |

| Construction                  |              |
|-------------------------------|--------------|
| Optical system                | Greenough    |
| Tube type                     | Binocular    |
| Tube angle of inclination     | 45°          |
| Tube 360° rotation            | ✓            |
| Contrasting methods           | Bright field |
| Interpupillary distance [Min] | 52 mm        |
| Interpupillary distance [Max] | 76 mm        |
| Diopter adjustment            | both-sided   |
| Diopter adjustment [Min]      | -6           |
| Diopter adjustment [Max]      | 6            |

| Ocular                |  |
|-----------------------|--|
| Ocular type           | Eyepiece HSWF 10 x / Ø 23mm with anti-fungus, high eye point |
| Ocular field width    | HSWF   |
| Eye point             | High Eye Point   |
| Ocular magnifications | 10 x   |
| Ocular visual field   | 23 mm  |
| Ocular diameter       | 30 mm  |
| Objective             |  |

0,7 x - 4,5 x

Objectives magnifications

| rersal stand and illumination for your functional |   |  |  |  |
|---|---|--|--|--|
|   | Illumination                                    |  |  |  |
|   | Illuminance                                     | Reflected light                          |  |  |
|   | Illumination type incident light                | LED                                      |  |  |
|   | Illumination intensity incident light           | 4,5 W                                    |  |  |
|   | Illumination dimmable                           | Incident light                           |  |  |
|   | Focussing                                       |  |  |  |
|   | Field of view [Min]                             | 5,1 mm                                   |  |  |
|   | Field of view [Max]                             | 32,8 mm                                  |  |  |
|   | Standard total magnification [Min]              | 7 x                                      |  |  |
|   | Standard total magnification [Max]              | 45 x                                     |  |  |
|   | Zoom [Min]                                      | 0,7 x                                    |  |  |
|   | Zoom [Max]                                      | 4,5 x                                    |  |  |
|   | Sample height [Max]                             | 130 mm                                   |  |  |
|   | Torque regulation                               | ✓  |  |  |
|   | Working distance                                | 110 mm                                   |  |  |
|   | Magnification ratio                             | 6,4:1                                    |  |  |
|   | Focusing mechanism                              | coarse drive                             |  |  |
|   | Stereomicroscope stand                          |  |  |  |
|   | Stand type                                      | universal (spring loaded arm with clamp) |  |  |
|   | Diameter mounting microscope head $(\emptyset)$ | 76 mm                                    |  |  |

| Power Supply  |  |
|---|--|
| Plug-in power supply type   | Built-in power supply                  |
| Plug-in power supply / adapter for countries - optional                     | EURO<br>AUS<br>UK<br>US<br>CH          |
| Input voltage power supply / power [Max]                                    | 100 - 240 V                            |
| Input voltage device / power [Max]  | 100 - 240 V                            |
| Power socket for mains adapter  | Protective contact plug                |
| Input voltage power supply / power [Max] Input voltage device / power [Max] | US<br>CH<br>100 - 240 V<br>100 - 240 V |

Environmental conditions

Storage temperature [Min]

Storage temperature [Max]

| Packing & Shipping           |                |
|------------------------------|----------------|
| Delivery time                | 1 d            |
| Dimensions packaging (W×D×H) | 700×520×350 mm |
| Shipping method              | Parcel service |
| Net weight approx.           | 6 kg           |
| Gross weight approx.         | 10 kg          |

-5 °C

40 °C

1

## **KERN OZM 982**



Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace

Shipping weight 25,5 kg

Pictograms