KERN **DAB 200-2**



Particularly user-friendly moisture analyzer with high-quality halogen quartz glass heater - ideal for recurring rapid tests



| Category | |
|--|--------------------------------|
| Brand | KERN |
| Product categoriy | Laboratory balance |
| Product group | Moisture analyser |
| Product family | DAB |
| Measuring System | |
| | Single renge helenee |
| Construction type of the scale | Single-range balance |
| Weighing system | Strain gauge |
| Weighing capacity [Max] | 200 g |
| Readability [d] | 0,01 g |
| Readability moisture [d] (%) | 0,05% |
| Temperature increment | 1 °C |
| Reproducibility | 0,01 g |
| Reproducibility weight of sample 2 g | 1,5% |
| Reproducibility weight of sample 10 g | 0,3% |
| Sample – Moisture content | 20% - 100% |
| Sample – Dry content | 100% - 20% |
| Linearity | ± 0,03 g |
| USP Minimum weight of sample (k = 2, $U = 0.1\%$) | 20 g |
| Resolution | 20.000 |
| Tare range | 200 g |
| Adjustment options | Adjusting with external weight |
| Recommended adjusting weight | 200 g (F2) |
| Possible calibration points | 200 g |
| Stabilization time | 3 s |
| Warm-up time | 30 min |
| Eccentric loading at 1/3 [Max] | 0,05 g |
| Maximum creep (15 minutes) | 40 mg |

| Maximum creep (30 minutes) | 80 mg |
|--|-------------------------|
| Default unit | g |
| | g |
| Units | % Humidity |
| | % Dry mass |
| Units (if device is conformity | g |
| assessed) | - |
| Temperature [Min] (°C) | 40 °C 199 °C |
| Temperature [Max] (°C) | .,,, C |
| Load cell connection | 4-wire |
| Display | |
| | |
| Display type | graphic |
| Display backlight | |
| Display screen size | 5.4" |
| Display segments | 7 |
| Display digit height - smallest digit | 6 mm |
| Display digit height | 14 mm |
| Construction | |
| Dimensions completely mounted | 240×245×100 mm |
| (W×D×H) | 240×365×180 mm |
| Dimensions weighing surface (Ø) | 92 mm |
| Dimensions weighing surface | 92 mm |
| Material housing | cast aluminium, plastic |
| Material weighing plate | aluminium sample plates |
| Material load cell(s) | aluminium |
| Level indicator | \checkmark |
| Levelling feet adjustable | ✓ |
| Heat generation capacity (W) | 400 |
| Functions | |
| Functions | |
| | Standard drying |
| Drying modes | Rapid drying |
| Manager, guadager of during | Gentle drying |
| Memory - number of drying programs | 15 |
| programs | time controlled |
| Switch-off criteria | automatic |
| | manual |
| Memory function | ✓ |
| Memory - number of results | 5 |
| | |
| | _ |
| Memory - number of sample (descriptions) | 5 |
| Memory - number of sample (descriptions) | - |
| Memory - number of sample | 5 off |
| Memory - number of sample (descriptions) Auto-off interval(s) in mains power | - |
| Memory - number of sample (descriptions) Auto-off interval(s) in mains power mode | off |

KERN **DAB 200-2**



Particularly user-friendly moisture analyzer with high-quality halogen quartz glass heater - ideal for recurring rapid tests

| Interface | |
|---|--|
| Interfaces | RS-232 standard |
| Power Supply | |
| Supplied power supply Plug-in power supply type | Power supply unit Built-in power supply |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| Plug-in power supply / adapter for countries - optional | UK |
| Input voltage power supply / power [Max] | 230 V AC, 50 Hz |
| Input voltage device / power [Max] | 230 V AC, 50 Hz |
| Power socket for mains adapter | Power supply cable |
| Battery | no battery |
| Environmental conditions | |
| Ambient temperature [Min] | 5 °C |
| Ambient temperature [Max] | 40 °C |
| Humity of environment [Min] | 5 % |
| Humity of environment [Max] | 80 % |
| Approval | |
| CE mark | ✓ |
| Services (optional) | |
| Article number for DAkkS calibration | 963-127 |
| Article number for factory calibration (temperature) | 964-305 |
| Article number for certificate of conformity | 969-517 |
| Packing & Shipping | |
| Delivery time | 1 d |
| Dimensions packaging (W×D×H) | 490×350×360 mm |
| Shipping method | Parcel service |
| Net weight approx. | 5,0 kg |
| a | |

8 kg

12,3 kg

Gross weight approx.

Shipping weight

Pictograms

STANDARD



OPTION

