## KERN CH 50K50



## The classic among manual hanging scales - perfect for rapid weighing of higher loads



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Hanging scale
Product family	СН
Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	50 kg
Readability [d]	0,05 kg
Reproducibility	0,05 kg
Linearity	± 0,1 kg
Resolution	1.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	20 kg (M3)
Possible calibration points	20 kg
Stabilization time	2 s
Warm-up time	10 min
Eccentric/Off-centre loading is not possible	1
Construction type of the scale	Single-range balance
Units	kg Ib N
Internal measuring frequency	5 Hz
Tolerance (% of [Max])	0,5%
Maximum creep (15 minutes)	100 g
Maximum creep (30 minutes)	200 g
Default unit	kg

Display	
Display type	LCD
Display backlight	no
Display digit height	11 mm
Construction	
Dimension housing (W×D×H)	90×30×176,5 mm
Dimensions completely mounted (W×D×H)	90×30×283 mm
Dimensions housing - width (A)	90 mm
Dimensions housing - depth (B)	30 mm
Dimensions housing - height/ length (C)	176,5 mm
Dimensions - total height/total length (D)	283 mm
Material housing	plastic
Material load hook	steel
Material display housing	plastic
Load cells - number	1
Functions	
Underfloor weighing	None
Function for averaging under unstable weighing conditions	1
Hold function	$\checkmark$
Auto-off interval(s) in battery mode/rechargeable battery mode	3:30 min
Auto-off interval(s) in mains power mode	3 min
Tare function	manual (multi)
Number of keys for operation	3
Power Supply	
Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	9 V block
Battery connection	9V Bloc
Battery operating time	80 h
Battery voltage	9 V
Environmental conditions	
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Humity of environment [Max]	80 %
Storage temperature [Max]	60 °C

## KERN CH 50K50



The classic among manual hanging scales - perfect for rapid weighing of higher loads

Approval		
CE mark	1	
TÜV-tested	1	
Services (optional)		
Article number for adjustment at the location of installation	961-248	
Article number for DAkkS calibration	963-128H	
Article number for certificate of conformity	969-517	
Packing & Shipping		
Delivery time	1 d	
Dimensions packaging (W×D×H)	225×150×70 mm	
Shipping method	Parcel service	
Net weight approx.	0,35 kg	
Gross weight approx.	0,65 kg	
Shipping weight	0,615 kg	
Product information		
GTIN/EAN number	4045761027190	
Pictograms		
STANDARD		
CAL EXT UNIT MOVE BATT DMS 1 DAY		

OPTION

