SAUTER DA 10-3



Comfortable testing of screw tops, e.g. bottles, jars etc.



Category	
Brand	Sauter
Product categoriy	Torque measuring device
Product group	Torquemeter for Twist Locks
Product family	DA

Measuring System	
Measuring range torque [Min]	0,5 Nm
Measuring range torque [Max]	10 Nm
Readability torque [d] (Nm)	0,002 Nm
Test object diameter [Max]	16 cm
Overload protection (% of [Max])	120%
Units	Nm, kgf/cm, kgf/m, in/ lbs, ft/lbs
Internal data memory: Number of individual values	500
Internal data memory: Number of value groups	1
Internal measuring frequency	1000 Hz
Tolerance (% of [Max])	0,5%

Tolerance (% or [wax])	0,5%
Display	
Display type	LCD graphic
Display resolution	128×64
Construction	
Dimension (W×D×H)	100×160×250 mm
Dimension housing (W×D×H)	250×160×100 mm
Material housing	metal, lacquered
Functions	
Limit-setting function	✓

Peak function	✓
Memory function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	1 - 60 min

Interface

calibration

Interfaces	RS-232 standard USB-Device
Power Supply	
Supplied power supply Plug-in power supply type	Accu & Power supply Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V
Input voltage device / power [Max]	9 V, 500 mA
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 10,8 mm
Battery / accumulator type	NiMH
Battery connection	2-pole tub connector
Battery capacity	750 mAh
Battery voltage	4,8 V
Rechargeable battery operating time - backlight off	18 h
Rechargeable battery charging time	14 h
Environmental conditions	
Ambient temperature [Min]	15 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C
Approval	
CE mark	✓
Services (optional)	
Article number for factory	961-120

SAUTER DA 10-3



Comfortable testing of screw tops, e.g. bottles, jars etc.

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	375×321×110 mm
Shipping method	Parcel service
Net weight approx.	3,0 kg
Gross weight approx.	3,8 kg
Shipping weight	3,7 kg

Pictograms

STANDARD



OPTION



230 V 1 DAY